

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product form : Mixture  
 Product name : **Floor Cleaner**  
 Product code : C-F01

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Floor Cleaner

**1.3. Details of the supplier of the safety data sheet**

HD Chem  
 707 W. 16th St.  
 Long Beach, CA 90813  
 T (888) 443-2436 - F (562) 495-7716

**1.4. Emergency telephone number**

Emergency number : (888) 443-2436

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (GHS-US)**

Skin Corr. 1C H314  
 Eye Dam. 1 H318  
 Full text of H-phrases: see section 16

**2.2. Label elements**

**GHS-US labeling**

Hazard pictograms :



GHS05

Signal word : **Danger**

Hazard statements : Causes severe skin burns and eye damage.  
 Causes serious eye damage.

Precautionary statements : Do not breathe mist, vapors.  
 Wash hands and forearms thoroughly after handling.  
 Wear eye protection, face protection, protective clothing, protective gloves.  
 If swallowed: rinse mouth. Do NOT induce vomiting.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Immediately call a POISON CENTER or doctor/physician.  
 Wash contaminated clothing before reuse.  
 Store locked up.  
 Dispose of contents/container in accordance with Local, State, and Federal regulations.

**2.3. Hazard not otherwise classified (HNOC)**

No additional information available

**2.4. Unknown acute toxicity (GHS-US)**

No data available

**SECTION 3: Composition/information on ingredients**

**3.1. Substance**

Not applicable

(NOTE: If component displays the \* (asterisk) symbol, the following statement applies.)

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-phrases: see section 16

**3.2. Mixture**

Name	Product identifier	%	Classification (GHS-US)
sodium xylenesulfonate	(CAS No) 1300-72-7	1 - 5	Skin Irrit. 2, H315 STOT SE 3, H335
sodium hydroxide	(CAS No) 1310-73-2	1 - 5	Met. Corr. 1, H290 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314
2-(2-butoxyethoxy)ethanol	(CAS No) 112-34-5	1 - 5	Eye Irrit. 2A, H319
alcohol alkoxylate*		1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

(NOTE: If component displays the \* (asterisk) symbol, the following statement applies.)

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

**4.2. Most important symptoms and effects, both acute and delayed**

- Symptoms/injuries : Causes severe skin burns and eye damage.
- Symptoms/injuries after skin contact : Causes burns/corrosion of the skin.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : Burns to the gastric/intestinal mucosa. Abdominal pain. Gastrointestinal complaints.

**4.3. Indication of any immediate medical attention and special treatment needed**

No additional information available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

- Suitable extinguishing media : Alcohol-resistant foam. BC powder. Carbon dioxide. Dry chemical powder. Sand/earth.
- Unsuitable extinguishing media : No unsuitable extinguishing media known.

**5.2. Special hazards arising from the substance or mixture**

- Reactivity : Reacts with (strong) oxidizers. On burning: release of (highly) toxic gases/vapors. Reacts violently with (some) acids: release of heat.

**5.3. Advice for firefighters**

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : No additional information available.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

- General measures : Isolate from fire, if possible, without unnecessary risk.

**6.1.1. For non-emergency personnel**

- Protective equipment : Protective goggles.  
Protective gloves.  
Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel.

**6.1.2. For emergency responders**

- Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

**6.2. Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

**6.3. Methods and material for containment and cleaning up**

For containment : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. If reacting: dilute toxic gas/vapor with water spray.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Small quantities of liquid spill: neutralize with dilute acid solution. Wash down leftovers with plenty of water. Wash clothing and equipment after handling.

**6.4. Reference to other sections**

See Heading 8. Exposure controls and personal protection.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe mist, vapors. Ensure good ventilation of the work station. Observe normal hygiene standards. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and forearms thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**7.2. Conditions for safe storage, including any incompatibilities**

Technical measures : Provide local exhaust or general room ventilation. Comply with applicable regulations.

Incompatible products : Acids. Oxidizing agent.

Storage area : Store in a cool, dry well-ventilated area. Keep container tightly closed when not in use.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>		
ACGIH	ACGIH TWA (ppm)	10 ppm
ACGIH	ACGIH STEL (ppm)	10 ppm
<b>sodium hydroxide (1310-73-2)</b>		
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³

**8.2. Exposure controls**

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. In case of insufficient ventilation, wear suitable respiratory equipment.

Other information : When using, do not eat, drink or smoke.

Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state : Liquid

Color : Clear green

Odor : Mild

Odor threshold : No data available

pH : 13 - 14

Melting point : No data available

Freezing point : No data available  
 Boiling point : > 212 °F  
 Flash point : > 200 °F  
 Relative evaporation rate (butyl acetate=1) : No data available  
 Flammability (solid, gas) : No data available  
 Explosive limits : No data available  
 Vapor pressure : No data available  
 Vapor density : No data available

Specific Gravity @ 77° F : 1.065 - 1.085  
 Solubility : Soluble in water.  
 Partition Coefficient n-Octanol-Water : No data available  
 Auto-ignition temperature : No data available  
 Decomposition temperature : No data available  
 Viscosity : No data available

**9.2. Other information**

VOC content : < 1 g/l CARB VOC

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Reacts with (strong) oxidizers. On burning: release of (highly) toxic gases/vapors. Reacts violently with (some) acids: release of heat.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reacts vigorously with strong oxidizers and acids. Contact with halogenated compounds may liberate toxic gas.

**10.4. Conditions to avoid**

Extremely high or low temperatures.

**10.5. Incompatible materials**

Strong acids. Oxidizers.

**10.6. Hazardous decomposition products**

Carbon dioxide. Carbon monoxide. Nitrogen oxides. Sulfur oxides. Thermal decomposition generates : Corrosive vapors.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

Acute toxicity : Not classified

<b>sodium xylenesulfonate (1300-72-7)</b>	
LD50 oral rat	3346 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE US (oral)	3346.000 mg/kg body weight
<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
LD50 oral rat	5660 mg/kg (Rat)
LD50 dermal rabbit	2764 mg/kg (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	5660.000 mg/kg body weight
ATE US (dermal)	2764.000 mg/kg body weight
<b>sodium hydroxide (1310-73-2)</b>	
LD50 dermal rabbit	1350 mg/kg (Rabbit; Literature)
ATE US (dermal)	1350.000 mg/kg body weight
<b>alcohol alkoxylate</b>	
LD50 oral rat	> 2000 mg/kg

Skin corrosion/irritation : Causes severe skin burns and eye damage.  
 pH: 13 - 14

Serious eye damage/irritation : Causes serious eye damage.  
 pH: 13 - 14

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met
Symptoms/injuries after skin contact	: Causes burns/corrosion of the skin.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Burns to the gastric/intestinal mucosa. Abdominal pain. Gastrointestinal complaints.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>sodium xylenesulfonate (1300-72-7)</b>	
LC50 fish 1	> 1580 mg/l (Rainbow trout)
EC50 Daphnia 1	> 1020 mg/l
ErC50 (algae)	758 mg/l
NOEC chronic algae	240 mg/l
<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
LC50 fish 1	1300 mg/l (96 h; Lepomis macrochirus)
LC50 other aquatic organisms 1	10 - 100 mg/l (96 h)
EC50 Daphnia 1	2850 mg/l (24 h; Daphnia magna; GLP)
LC50 fish 2	1805 mg/l (48 h; Leuciscus idus)
EC50 Daphnia 2	> 100 mg/l (48 h; Daphnia magna)
TLM fish 1	10 - 100,96 h; Pisces
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	53 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	>= 100 mg/l (96 h; Scenedesmus subspicatus)
<b>sodium hydroxide (1310-73-2)</b>	
LC50 fish 1	45.4 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Solution >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h; Ceriodaphnia sp.; Nominal concentration)
LC50 fish 2	189 mg/l (48 h; Leuciscus idus)
TLM fish 1	99 mg/l (48 h; Lepomis macrochirus)
TLM fish 2	125 ppm (96 h; Gambusia affinis)
<b>alcohol alkoxyate</b>	
EC50 Daphnia 1	> 100 mg/l

### 12.2. Persistence and degradability

<b>sodium xylenesulfonate (1300-72-7)</b>	
Persistence and degradability	Biodegradability in water: no data available.
<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the substance available. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.25 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.08 g O <sub>2</sub> /g substance
ThOD	2.173 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.11 % ThOD

<b>sodium hydroxide (1310-73-2)</b>	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

**12.3. Bioaccumulative potential**

<b>sodium xylenesulfonate (1300-72-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.

<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
BCF fish 1	0.46 (QSAR)
Log Pow	0.56 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>sodium hydroxide (1310-73-2)</b>	
Bioaccumulative potential	Bioaccumulation: not applicable.

**12.4. Other adverse effects**

Other information : Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Waste disposal recommendations : Dispose of contents/container in accordance with Local, State, and Federal regulations.  
 Ecology - waste materials : Avoid release to the environment.

**SECTION 14: Transport information**

**14.1. UN Number**

UN-No.(DOT) : 3266  
 Other information : Under 49 CFR 173.154(c) and (b)(2): This product may be shipped as ORM-D or Limited Quantity if the inner packagings do not exceed 5 L (1.3 gallons) or 5.0 kg (11 lbs). This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.

**14.2. UN proper shipping name**

DOT Proper Shipping Name : UN3266, Corrosive Liquid, Basic, Inorganic, N.O.S. (Sodium Hydroxide), 8, PGIII  
 Hazard labels (DOT) : 8 - Corrosive



**SECTION 15: Regulatory information**

**15.1. US Federal regulations**

<b>sodium xylenesulfonate (1300-72-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

<b>2-(2-butoxyethoxy)ethanol (112-34-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

<b>sodium hydroxide (1310-73-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

<b>sodium hydroxide (1310-73-2)</b>	
RQ (Reportable quantity, section 101(14) of CERCLA as published on EPA's List of Lists) :	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

<b>alcohol alkoxyate</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

**15.2. International regulations**

**CANADA**

**EU-Regulations**

No additional information available

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

**Classification according to Directive 67/548/EEC or 1999/45/EC**

Not classified

**15.2.2. National regulations**

**15.3. US State regulations**

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Prop 65 Comments :Formaldehyde (CAS#50-00-0): <11 ppm

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment.

Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

**SECTION 16: Other information**

Abbreviations Legend:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H290	May be corrosive to metals
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

**Disclaimer**

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*

Revision date: 08/2/2018

Supersedes: 03/27/2013

Version: 1.0